

空气绝缘开关柜用互感器

6-35kV 户内电流互感器

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

○ 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2
The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards

○ 额定绝缘水平：12/42/75kV ○ 额定二次电流：5A 或 1A
Rated insulation level 12/42/75kV Rated secondary current 5A or 1A

○ 额定频率：50Hz 或 60Hz ○ 环境温度：-5℃ ~+40℃
Rated frequency 50Hz or 60Hz Ambient temperature -5℃ ~+40℃



额定一次电流 Rated primary current (A)	一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated primary current (kA)	准确级组合 Accuracy classes combination	额定二次输出 Rated primary current (VA)					表面爬电距离 (mm)	重量 Weight (kg)	
				0.2S 0.5S	0.2	0.5	10P10	10P15			
5-200	$90I_n \times 10^{-3}$	$200I_n \times 10^{-3}$	0.2(S)/10P10 0.25(S)/10P10 0.2(S)/10P15 0.5(S)/10P15	10	10	10 20*	15	15	350	17	
300、400	24.5	44				10 20*					
500	32	80				10 15*					10 20*
600						10 15*					10 20*
800-1000	63	100			10 20*						

注：如果用户要求的参数超出上表范围，可与我公司协商后确定。
Note: If the required parameter is beyond the above range, it can be discussed and confirmed with us.

外形及安装尺寸 Overall dimension drawing

