

### 环网柜、充气柜用互感器

6-35kV 户内电压互感器

户内 三相 环氧树脂浇注式

INDOOR THREE-PHASE EPOXY RESIN CASTING TYPE

#### 技术参数 Technical data

- 产品性能符合标准：GB/T20840.1、3 和 IEC61869-1、3  
The voltage transformers are in accordance with GB/T20840.1、3 and IEC61869-1、3 standards
- 额定频率：50Hz 或 60Hz  
Rated frequency 50Hz or 60Hz
- 环境温度：-5℃ ~+40℃  
Ambient temperature -5℃ ~+40℃



环网柜充气柜用互感器

型号 Type	额定电压比 (V) Rated voltage ratio	准确级及准确级组合三相额定二次输出 (VA) Accuracy class and accuracy class combination Three-phase rated secondary output	极限输出 (VA) Limited output	额定绝缘水平 (kV) Rated insulation level	一次熔断器 (A) Once fuse	重量 (kg) weight	接线图 Wiring diagram
JSZV18-3R	3000/100	0.2---2×30 0.5---2×80 1---2×200	2×600	3.6/23/40	0.5	67	图 2 Figure 2
JSZV18-6R	6000/100			7.2/32/60			
JSZV18-10R	10000/100			12/42/75	0.2		
JSZV18-3R	3000/100/100	0.2/0.2-2×15/2×15	2×400 2×400	3.6/23/40	0.5		图 3-4 Figure 3-4
JSZV18-6R	6000/100/100	0.2/0.5-2×15/2×20		7.2/32/60			
JSZV18-10R	10000/100/100	0.5/0.5-2×40/2×40	2×400 2×600	12/42/75	0.2		
	10000/100/220	0.2/3---2×30/2×300 0.5/3---2×80/2×300					

#### 外形及安装尺寸 Overall dimension drawing

