

### 户外用互感器

6-35kV

户外 单相 环氧树脂浇注式

OUTDOORS SINGLE-PHASE EPOXY RESIN CASTING TYPE

#### 技术参数 Technical data

- 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2  
The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards
- 额定绝缘水平：12/42/75kV      ○ 额定二次电流：5A 或 1A  
Rated insulation level 12/42/75kV      Rated secondary current 5A or 1A
- 额定频率：50Hz 或 60Hz      ○ 环境温度：-25℃ ~+40℃  
Rated frequency 50Hz or 60Hz      Ambient temperature -25℃ ~+40℃
- 污秽等级：II 级  
Pollution class: class II



额定一次电流 (A) Rated primary current	短时热电流 (kA/S) Short-time thermal current	额定动稳定电流 (kA) Rated dynamic current	准确级组合 Class combination	准确级及额定输出 (VA) COS φ=0.8 Accuracy class and rated output			表面爬电距离 (mm) Surface creepage distance	重量 (kg) Weight
				0.2(S)	0.5(S)	10P15		
40	6	15	0.2(S)/10P 0.5(S)/10P	10	10	15	580	25
50	7.5	19						
75	11.25	37.5						
100	15	38						
150	22.5	56						
200	25	62.5						
300-800	31.5	80						
1000-2000	63	130						

#### 外形及安装尺寸 Overall dimension drawing

