

组合互感器

6-35kV

户外 三相 环氧树脂浇注式

OUTDOORS THREE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

○ 产品性能符合标准：GB/T20840.1、4 和 IEC61869-1、4
The voltage transformers are in accordance with GB/T20840.1、4 and IEC61869-1、4 standards

○ 额定频率 50Hz 或 60Hz
Rated frequency 50Hz or 60Hz

○ 环境温度：-25℃ ~+40℃ ○ 污秽等级 IV 级
Ambient temperature -25℃ ~+40℃ Pollution class IV



型号 Type	额定电压比 (V) Rated voltage ratio	准确级及准确级组合额定二次输出 (VA) Accuracy class and accuracy class combination rated secondary output	极限输出 (VA) Limited output	额定绝缘水平 (kV)Rated insulation level	表面爬电距离 (mm) Surface creepage distance	重量 (kg) Weight	接线图 Wiring diagram
JLSZY-6A JLSZY-6B	6000/100	0.2---20 0.5---50	600	7.2/32/60	830	101	图 10 Figure 10
	单相原件电压比: $\frac{6000}{\sqrt{3}} / \frac{100}{\sqrt{3}}$	0.2---15 0.5---30	400				
JLSZY-10A JLSZY-10B	10000/100	0.2---20 0.5---50	600	12/42/75	830	101	图 10 Figure 10
	单相原件电压比: $\frac{10000}{\sqrt{3}} / \frac{100}{\sqrt{3}}$	0.2---15 0.5---30	400				

额定电流比 (I1n/5) Rated transformation ratio		一秒钟热电流 (kA 有效值) Ith/is(kA r.m.s.)	动稳定电流 (kA 峰值) Idyn(kA peak)	准确级及额定二次输出 (VA) Accuracy class and rated secondary output
复变比 Double transformation ratio	单变比 Single transformation ratio			
7.5-10-15/5	7.5/5	1.0	2.5	0.2(S)---10 0.5S---10 0.5---15
10-15-20/5	10/5	1.5	3.75	
15-20-30/5	15/5	2.0	6	
20-30-40/5	20/5,25/5	2.7	6.75	
30-40-50/5	30/5	3.0	7.5	
40-50-75/5	40/5	4.5	20	
50-75-100/5	50/5	8.1	22.5	
75-100-150/5	75/5	10.8	30	
100-150-200/5	100/5	16.2	40	
150-200-300/5	150/5	24	60	
200-300-400/5	200/5,250/5	32	80	
300-400-500/5	300/5	45		
400-500-600/5	400/5	60	100	
500-600-800/5	500-1000/5	80		
600-800-1000/5				